
[illegible]

01 FC:208
02 FC:209
03 FC:210

82.00 CH

395.00 OP
369.00 OP
809.00 OP

POST
only

71479 U.S. PTO



05/27/98

Please type a plus sign (+) inside this box → ☒395-208
891-209
287-209

PTO/SB/50 (4/98)

Approved for use through 09/30/2000. OMB 0651-0033

Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

REISSUE PATENT APPLICATION TRANSMITTAL

Address to:

Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

Attorney Docket No.	62-575
First Named Inventor	Lin
Original Patent Number	5,520,679
Original Patent Issue Date (Month/Day/Year)	May 28, 1996
Express Mail Label No.	

APPLICATION FOR REISSUE OF:
(check applicable box)

Utility Patent



Design Patent



Plant Patent

APPLICATION ELEMENTS

1. ☒ * Fee Transmittal Form (PTO/SB/56)
(Submit an original, and a duplicate for fee processing)
2. ☒ Specification and Claims (amended, if appropriate)
3. ☒ Drawing(s) (proposed amendments, if appropriate)
4. ☒ Reissue Oath / Declaration (original or copy)
(37 C.F.R. § 1.175)(PTO/SB/51 or 52)
5. Original U.S. Patent
☒ Offer to Surrender Original Patent (37 C.F.R. § 1.178)
(PTO/SB/53 or PTO/SB/54)
or
☐ Ribboned Original Patent Grant
☐ Affidavit / Declaration of Loss (PTO/SB/55)
6. Original U.S. Patent currently assigned?
☒ Yes ☐ No
(If Yes, check applicable box(es))
☒ Written Consent of all Assignees (PTO/SB/53 or 54)
☒ 37 C.F.R. § 3.73(b) Statement ☒ Power of Attorney

ACCOMPANYING APPLICATION PARTS

7. ☐ Foreign Priority Claim (35 U.S.C. 119)
(if applicable)
8. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
9. ☐ English Translation of Reissue Oath/Declaration
(if applicable)
10. ☒ * Small Entity Statement(s) ☐ Statement filed in prior application,
(PTO/SB/09-12) Status still proper and desired
11. ☒ Preliminary Amendment
12. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
13. ☒ Other: Request For Transfer of Original Drawings

* NOTE FOR ITEMS 1 & 10: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28).

14. CORRESPONDENCE ADDRESS

☒ Customer Number or Bar Code Label

20736

or

☐ Correspondence address below

(Insert Customer No. or Attach bar code label here)

Name

Address

City

State

Zip Code

Country

Telephone

Fax

NAME (Print/Type)

William H. Bollman

Registration No. (Attorney/Agent)

36,457

Signature

Will H. Boll

Date

May 27, 1998

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

REISSUE APPLICATION FEE TRANSMITTAL FORM

Docket Number (Optional)

62-575

Claims as Filed - Part 1

Claims in Patent	For	Number Filed in Reissue Application	(3) Number Extra	Small Entity		Other than a Small Entity	
				Rate	Fee	Rate	Fee
(A) 23	Total Claims (37 CFR 1.16(j))	(B) 104	**** 81	= x \$11 =	891	or	x \$ =
(C) 1	Independent Claims (37 CFR 1.16(i))	(D) 10	* 7	= x \$41 =	287		x \$ =
Basic Fee (37 CFR 1.16(h))					\$395		\$
Total Filing Fee					\$1573	OR	\$

Claims as Amended - Part 2

	(1) Claims Remaining After Amendment		(2) Highest Number Previously Paid For	(3) Extra Claims Present	Small Entity		Other than a Small Entity	
					Rate	Fee	Rate	Fee
Total Claims (37 CFR 1.16(j))	***	MINUS	**	=	x \$ =	or	x \$ =	
Independent Claims (37 CFR 1.16(i))	***	MINUS	*****	=	x \$ =		x \$ =	
Total Additional Fee					\$	OR	\$	

* If the entry in (D) is less than the entry in (C), Write "0" in column 3.

** If the "Highest Number of Total Claims Previously Paid For" is less than 20, Write "20" in this space.

*** After any cancellation of claims

**** If "A" is greater than 20, use (B - A); if "A" is 20 or less, use (B - 20).

***** "Highest Number of Independent Claims Previously Paid For" or Number of Independent Claims in Patent (C).

☐ Please charge Deposit Account No. _____ in the amount of _____.
A duplicate copy of this sheet is enclosed.

☒ The Commissioner is hereby authorized to charge any additional fees under 37 CFR 1.16 or 1.17 which may be required, or credit any overpayment to Deposit Account No. 06-0115.
A duplicate copy of this sheet is enclosed.

☒ A check in the amount of \$ 1573 to cover the filing / additional fee is enclosed.

May 27, 1998
Date

William H. Bollman
Signature of Applicant, Attorney or Agent of Record

William H. Bollman
Typed or printed name

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Reissue Application of
Lin

Patent No. 5,520,679

Issued: May 28, 1996

For: OPTHALMIC SURGERY METHOD USING NON-CONTACT SCANNING
LASER

* * * * *

May 27, 1998

REQUEST FOR TRANSFER OF ORIGINAL DRAWINGS

Hon. Assist. Commissioner of Patents
and Trademarks
Washington, D.C. 20231

Sir:

It is respectfully requested that the original, formal drawings in Applicant's U.S.
Patent No. 5,520,679 issued to Lin, entitled OPTHALMIC SURGERY METHOD
USING NON-CONTACT SCANNING LASER, be transferred to this reissue application.

Please charge any insufficient or missing fee to our Account No. 06-0115, under
order No. 62-575.

Respectfully submitted,

Farkas & Manelli, PLLC

By William H. Bollman
William H. Bollman
Reg. No.: 36,457
Tel. No.: (202) 261-1020
Fax. No.: (202) 887-0336

Customer No. 20736

Reissue Application of Lin

Patent No. 5,520,679

Issued: May 28, 1996

For: OPHTHALMIC SURGERY METHOD USING NON-CONTACT SCANNING LASER

May 27, 1998

PRELIMINARY AMENDMENT

Hon. Assist. Commissioner of Patents
and Trademarks
Washington, D.C. 20231

Sir:

Please preliminarily amend the subject reissue application as follows:

IN THE CLAIMS:

Please amend claims 100-104 as follows:

Claim 100, line 1, replace "100" with -- 99 --.

Claim 101, line 1, replace "100" with -- 99 --.

Claim 102, line 1, replace "100" with -- 99 --.

Claim 103, line 1, replace "100" with -- 99 --.

Claim 104, line 1, replace "100" with -- 99 --.

Do Not
Enter

Year	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100
1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	

Consideration and allowance of the subject application are respectfully requested.

Claims 1 - 104 are pending in the application

Claims 100 - 104 have been amended to correct minor informalities.

Early and favorable action on the merits are respectfully requested.

Farkas & Manelli, PLLC

By William H. Bollman
William H. Bollman
Reg. No.: 36,457
Tel. No.: (202) 261-1020
Fax. No.: (202) 887-0336

Customer No. 20736

APPLICATION UNDER UNITED STATES PATENT LAWS

Invention: OPTHALMIC SURGERY METHOD USING NON-CONTACT
SCANNING LASER

Inventor(s): J. T. Lin

Farkas & Manelli P.L.L.C.
2000 M. Street, N.W., 7th Floor
Washington, D.C. 20036-3307

This is a:

- ☐ Provisional Application
- ☐ Regular Utility Application
- ☐ Continuing Application
- ☐ PCT National Phase Application
- ☐ Design Application
- ☒ Reissue Application
- ☐ Plant Application

SPECIFICATION

OPHTHALMIC SURGERY METHOD USING NON-CONTACT SCANNING LASER

This application is a continuation-in-part application of
Ser. No. 07/985,617, filed Dec. 3, 1992 now abandoned. 5

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to laser ophthalmic surgery 10
using a compact, low-cost, low-power laser system with a
computer-controlled, non-contact process and corneal
topography to perform corneal reshaping using either sur-
face ablation or thermal coagulation.

2. Prior Art 15

Various lasers have been used for ophthalmic applications
including the treatments of glaucoma, cataract and refractive
surgery. For non-refractive treatments (glaucoma and cata-
ract), suitable laser wavelengths are in the ranges of visible
to near infrared. They include: Nd:YAG (1064 nm), 20
doubled-YAG (532 nm), argon (488, 514 nm), krypton (568,
647 nm), semiconductor lasers (630-690 nm and 780-860
nm) and tunable dye lasers (577-630 nm). For refractive
surgeries (or corneal reshaping), ultraviolet (UV) lasers
(excimer at 193 nm and fifth-harmonic of Nd:YAG at 213 25
nm) have been used for large area surface corneal ablation
in a process called photorefractive keratectomy (PRK).
Corneal reshaping may also be performed by laser thermal
coagulation currently conducted with Ho:YAG lasers using
a fiber-coupled, contact-type process. However, the existing 30
ophthalmic lasers as above described have one or more of
the following limitations and disadvantages: high cost due to
the high-power requirement in UV lasers for photorefractive
keratectomy; large size and weight; high maintenance cost
and gas cost (for excimer laser), and high fiber-cost for 35
contact-type laser coagulation.

In light of the above, it is an object of the present
invention to provide ophthalmic laser systems which offer
the advantages of: low-cost, reduced size and weight, reli- 40
ability, easy-operation and reduced maintenance. Another
object of this invention is to provide a computer-controlled
scanning device which enables use of a low-cost, low-
energy laser for photorefractive keratectomy currently per-
formed only by high-power UV lasers.

It is yet another object of the present invention to provide 45
a refractive laser system which is compact, portable and
insensitive to environmental conditions (such as vibration
and temperature). This portable system may also be used for
a mobile clinical center where the laser is transported by a 50
van. It is yet another objective of the present invention to
provide a non-contact process for corneal reshaping using
laser thermal coagulation, where predetermined corneal
correction patterns are conducted for both spherical and
astigmatic changes of the corneal optical power.

The prior U.S. Pat. No. 4,784,135 to Blum, et al. and 55
assigned to IBM teaches the first use of far ultraviolet
irradiation of a biological layer to cause ablative photode-
composition. This patent teaches that using a laser beam
housing a wavelength of 193 nm and an energy level of 60
much greater than 10 mJ/cm²/pulse can be used to photoa-
blate corneal tissue without the build up of excess heat. The
present invention on the other hand uses a process that
allows the use of energy levels of less than 10 mJ/pulse in
a process that still allows photoablation. 65

There are several prior art U.S. Patents relating to refrac-
tive surgery, or photorefractive keratectomy. A UV solid-

360050 "F4463663
000050" 44463663

state fifth-harmonic of Nd:YAG (or Nd:YLF) laser at 213 nm (or 210 nm), is disclosed in U.S. Pat. No. 5,144,630 by the inventor, J. T. Lin. U.S. Pat. No. 4,784,135 suggests the use of a UV laser with wavelengths less than 200 nm, in particular Argon Fluoride (ArF) laser at 193 nm, for non-thermal photoablation process in organic tissue. Devices for beam delivery and methods of corneal reshaping are disclosed in U.S. Pat. No. 4,838,266 using energy attenuator, and U.S. Pat. No. 5,019,074 using an erodible mask. Techniques for corneal reshaping by varying the size of the exposed region by iris or rotating disk are discussed in Marshall et al, "Photoablative Reprofile of the Cornea Using an Excimer Laser: Photorefractive Keratectomy" Vol. 1, Lasers in Ophthalmology, pp. 21-48 (1986). Tangential corneal surface ablation using ArF excimer laser or harmonics of Nd:YAG laser (at 532 and 266 nm) is disclosed in U.S. Pat. No. 5,102,409.

This prior art however requires high UV energy of (100-300 mJ) per pulse from the laser cavity or (30-40) mJ per pulse delivered onto the corneal surface, where large area corneal ablation using a beam spot size of about (4-6) mm which gives an energy density of (120-200) mJ/cm². Moreover, the prior art Argon Fluoride excimer lasers operate at a repetition rate of (5-15) Hz and also limit the practical use of the tangential ablation concept which takes at least (5-10) minutes for a -5 diopter corneal correction in a 5-mm optical zone. The high energy requirement of the currently used Argon Fluoride excimer laser suffers the problems of: high-cost (in system, erodible mask and gas cost), high-maintenance cost, large size/weight and system are sensitive to environmental conditions (such as temperature and moisture).

The prior L'Esperance patent, U.S. Pat. No. 4,665,913, disclosed the method of a scanning laser for corneal reshaping. The proposed concept of this prior art, however, had never been demonstrated to be practical or to achieve the desired clinical requirement of smooth ablation of the corneal surface. This prior art is not practically useful and had not ever been demonstrated to be real because of the conditions in the art. A high-power laser of (100-200 mJ) is required in the prior art in order to obtain a useful beam with a substantially square spot size of 0.5x0.5 mm (see prior art, Col. 3, line 65 and Col. 4, lines 1-14) due to the low efficiency of obtaining such a beam, and which further requires a substantially uniform density (see Col. 13, line 30 and Col. 15, line 25). To achieve myopic correction, for example, the prior art (Col. 13, lines 61-66 and Col. 15 lines 60-65) proposes a smooth laser density increase with increasing scanning radius under the condition that a substantially uniform density of the scanning beam is required for a substantially uniform scan area (Col. 15, lines 20-28 of L'Esperance). Furthermore, L'Esperance teaches (Col. 4, lines 40-50) that a depth of 0.35 mm in an area of 6 mm diameter might be achieved in about 15 seconds when a beam spot of 0.5x0.5 mm is used and each pulse ablated 14 microns. The prior art proposes the method of having individual square beams (0.5x0.5 mm) scan to the fashion of exact matching of the square boundaries to cover the area of 6 mm, where the overlap among these individual beams should be avoided, otherwise excessive ablation near the boundaries of each 0.5x0.5 mm spot causes ridges. This is also part of the reason that the prior art requires a substantially square section of the individual beam with a substantially uniform density.

The L'Esperance U.S. Pat. No. 4,665,913 requires a complex apparatus to select a section of the beam which is substantially uniform in density within a substantially

20250744000
20250744000
20250744000

It is therefore a further object of the present invention to provide a method and apparatus for corneal reshaping by using software-driven new scanning patterns which do not require substantially uniform density or a specific spot shape. Contrary to L'Esperance's teachings, which suggest that there should be a perfect boundary match among each square beams and that excessive overlap should be avoided, the present invention proposes that a large portion (50%-80%) of overlap among the individual beams is necessary in order to achieve uniform ablated areas and a smooth profile without ridges. Furthermore, a low-power UV laser (0.1-2 mJ on corneal surface) at its bare-beam (having typically a 3-lop profile) without any beam reshaping is sufficient to achieve a smooth ablation surface based on the method proposed in the present invention, where computer-controlled beam overlap and orientation are employed. In addition to the surface quality problems, it is also impossible for L'Esperance to achieve any meaningful clinical results using his proposed techniques based on the present low-energy laser of (2-4) mJ from the output laser window and (0.1-2) mJ on corneal surface.

Therefore, another object of the present invention is to provide a new method of beam scanning which combines beam overlap and orientation for a random beam density distribution on the ablated corneal surface such that the individual beam profiles are not critical, where the focused beam (spot size of 0.1-1.2 mm) uses very low energy (0.1-2 mJ) and at its bare-profile is delivered onto the corneal surface in an averaged fashion. Uniform, near flat-top ablated areas of (1-9 mm in diameter) can be performed by

5 Ophthalmic Technologies II (1991), p.p. 266-275.

10 0.05–10 mJ per pulse, or about 10 to 100 times less than that of the prior art. This new concept enables one to make the refractive lasers at a lower cost, smaller size and with less weight (by a factor of 5–10) than that of prior art lasers. Furthermore, these compact lasers of the present invention
15 are portable and suitable for mobile clinical uses. To achieve beam uniformity and fast refractive surgery (30 to 60 seconds), a mathematical model of the beam overlap and ablation speed is also disclosed in the present invention.

art uses fiber-coupled contact-type procedure which involves the following drawbacks: (i) slow processing speed (typically a few minutes to perform eight-spot coagulation) which causes the non-uniform collagen shrinkage zone; (ii) circular coagulation zone which limits the procedure only for spherical type correction such as hyperopia; and (iii) the contact fiber-tip must be replaced in each procedure.

cedure under a non-contact mode and conduct the procedure many times faster than that of the prior contact-procedure and without cost for a fiber-tip replacement. Furthermore the coagulation patterns can be computer predetermined for specific applications in both spherical and astigmatic corrections. The flexible scanning patterns will also offer uniform and predictable collagen shrinkage.

40 intrastroma photokeratectomy (IPK), phototherapeutic keratotomy (PTK), and laser-assisted keratomileusis (LAK).

SUMMARY OF THE INVENTION

45 The preferred embodiments of the basic ophthalmic surgery method uses a laser system for the ophthalmic surgery process, including: (1) a diode-pumped solid-state lasers, Nd:YAG or Nd:YLF, which is frequency-converted by nonlinear crystals of KTP (potassium titanyl phosphate), LiB₃O₃ (lithium triborate), KNbO₃ (potassium niobate) and BBOT (beta barium borate) into the fifth-harmonic at wavelength 213 nm or 210 nm with energy of 0.01 to 5.0 mJ; (2) compact, low-cost, low-power (energy of 1 to 10 mJ per pulse) argon fluoride excimer laser at 193 nm; (3) a frequency-converted Alexandrite or Li:SAF or diode, lasers (193-220) nm; (4) a compact, low-cost, Q-switched Er:YAG laser at 2.94 microns; (5) a free-running Ho:YAG (at 2 microns) or Er:glass (at 1.54 microns) or diode laser (1.9-2.5 microns); (6) ultrashort pulse IR laser (750-1100 nm) and (7) mid-IR (2.5-3.2 microns) laser generated from optical parametric oscillation.

65 a spot size of (0.05–2) mm in diameter, where laser energy per pulse of (0.01–10) mJ is sufficient to achieve photo-ablation threshold (PAT) energy density of 50 to

5
10

15

20

25

30

35
40
45
50

55

60

65

FIG. 3 is a block diagram of a computer-controlled refractive laser system of Ho:YAG or Er:glass or diode laser in a non-contact scanning mode for laser thermokeratoplasty;

FIGS. 4A through 4E shows computer-controlled scanning patterns for photo-coagulation in non-contact LTK procedures for both spherical and astigmatic corneal reshaping;

FIGS. 5A and 5B are procedures for laser-assisted myopic keratomileusis and hyperopic keratomileusis, where the reshaping can be performed either on the inner or outer part of the tissue;

FIGS. 6A through 6D show computer-controlled beam overlap and scanning patterns for myopic, hyperopic and astigmatic correction using UV (193-240 nm) or IR (0.7-3.2 microns) lasers;

FIGS. 7A and B laser radial keratectomy patterns (LRK) using laser excisions for myopia (radial-cut) and astigmatism (T-cut);

FIGS. 8A through 8D show ablation patterns for refractive correction using predetermined coatings on UV or IR grade windows;

FIGS. 9A through 9B show the spatial overlap for uniform pattern;

FIGS. 10A through 10B show the beam orientation for smooth ablation; and

FIG. 11 shows the oriented expanding scanning to achieve the required ablation profiles, where the diameters are governed by a mathematical formula.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

The theoretical background of the present invention with regards to the beam overlap and ablation rate in photorefractive keratectomy, intrastroma photokeratectomy, synthetic epikeratoplasty, phototherapeutic keratectomy and myopic keratomileusis procedures described in the present invention is as follows.

Given a laser energy per pulse of m (in mJ), an intensity of I (in mJ/cm^2) may be achieved by focusing the beam into an area of A , where $I = E/A$. For corneal tissue ablation to occur requires the laser intensity (I) to be above the photoablation threshold (PAT), (60-120) mJ/cm^2 for UV-laser (193-215 nm) and (200-600) mJ/cm^2 for IR-laser (2.5-3.2 microns). Therefore it is always possible to tightly focus a laser beam and achieve the PAT value even for a low-energy laser (0.1-5) mJ. The drawback of using a low-energy, small-spot laser for large area ablation is that the operation time will be longer than that of a large-spot but high-power laser. However, time of operation may be shortened by using a high-repetition-rate laser (higher than 50 Hz). Small-spot, low-energy lasers for large area surface ablation would become practical only when a scanning device is used in a high-repetition-rate laser and only when uniform beam profile can be assured by the appropriate beam overlap. These two important issues are addressed in the present invention.

The overall operation rate (R) for a given diopter correction (D) is limited by the laser scanning rate (R_1) which is in turn limited by the laser repetition rate. In addition, R is also proportional to the tissue ablation rate (R_T) which is proportion to the laser intensity I (or energy density) at a given energy E .

The diopter change (D) in the case of myopia is related to the correction zone diameter (W) and the center ablation

Based upon the above-described theory, some important features are: (i) CW lasers (either UV or IR) with low intensity normally can not cause photo-ablation since the energy density is lower than the PAT value; (ii) Lasers (UV or IR) at Q-switched or mode-locked mode and with pulse-duration shorter than 100 nanosecond will normally achieve the intensity above the PAT even at low-energy level of 0.05–5 mJ. In particular, picosecond lasers at high repetition rate is desirable where energy in the microjoule range would be sufficient. Moreover, the Q-switched short pulse lasers have smaller thermal damage than that of free-running lasers. The cost-effective refractive lasers are those which have high repetition rate (50 Hz and up) but operated at low-energy (0.05–5 mJ) and short pulse duration (0.001–20 nanoseconds). The preferred embodiments disclosed in the present invention as discussed in FIG. 1 are based upon this theory. Beam focusing and scanning are always required to achieve the PAT and smooth ablation profile. The individual beam profile in the scanning system is not as critical as that in prior art lasers which require a uniform overall profile within the large ablation zone of (4–6) mm. In laboratory tests, we have achieved a very smooth ablation profile with zone diameter up to 8 mm starting from a non-uniform

focused beam profile which was randomly scanned over the ablation zone of (1-8) mm. Using overlap of (50-80)% of focused beam spot of (0.2-1.5) mm, and a typical number of pulses delivered to the corneal surface of 2,000-4,000, which assures a sufficient beam overlap for smooth profile and pulse to pulse energy fluctuation is not critical.

Referring to FIG. 1, a refractive laser system in accordance with the present invention comprises a basic laser 10 having UV (193-220 nm) or IR (0.7-3.2 microns) wavelength 11 coupled by a scanning device 12 having the beam from focusing optics 14 directed onto a reflecting mirror 15 into target 16 which target may be the cornea of an eye. An aiming system 17 has a visible wavelength (from a laser diode or He-Ne laser) 18 adjusted to be collinear with the ablation beam 11 and defines the centration of the beam onto the cornea surface at normal incident. The basic laser head 20 is steered by a motorized stage for X and Y horizontal directions 21 and the vertical (height) direction 22 which assures the focusing beam spot size and the centration of the beam onto the cornea. The system has a computer controlled panel 23 and wheels 24 for portable uses. The target 16 includes a human cornea for applications of photorefractive keratectomy, phototherapeutic keratectomy and laser radial keratotomy (using the UV 193, 210, 213 nm or IR 2.9 microns beam focused on the corneal surface area) and intrastroma photokeratectomy (using the 1064 or 1053 or 1047 nm beam, or their second-harmonic, focused into the intrastroma area), and synthetic or real corneal tissues for applications of synthetic epikeratoplasty and myopic keratomileusis. The computer controlling panel 23 also provides the synchronization between the scanning gavo (galvanometer scanner) and the laser repetition rate. A commercially available galvanometer scanner made by General Scanning, Inc. is used in scanning the laser beam.

The laser systems described herein have been demonstrated using photorefractive keratectomy procedure with a diopter corrections up to -6 in PMMA plasty and -12 in corneal tissues. In the case of PMMA, we have also measured the diopters by a lensmeter with well-defined readings in the ranges of -1 to -12 diopters. This data provides the evidence of predictable diopter corrections using the laser systems of the present invention. Furthermore, minimal tissue thermal damage of 0.3-1.0 microns were measured by TEM (transmission electron microscopy). In measurements, a multi-zone (MZ) approach for high-diopter corrections (8-12) was used, where the center zone is 3 mm and the correction power decreases when the zone increases from 4 mm to 6 mm. This multi-zone approach reduces the overall ablation thickness and hence reduces the haze effect.

Still referring to FIG. 1, the basic laser 10, according to the present invention, includes a compact, optically-pumped (either flash-lamp or laser-diode pumped) lasers of Nd:YAG, Nd:YLF or the self-frequency-doubling crystal of NYAB (neodymium yttrium aluminum) with pulse duration of 0.05-20 nanoseconds and repetition rate of 1-10,000 Hz. It is known that this basic laser 10 is available using a standard Q-switch or mode-lock, where the UV wavelength at 209-213 nm may be achieved by the frequency conversion techniques using nonlinear crystals disclosed by the inventor in U.S. Pat. No. 5,144,630. The UV laser energy required for efficient ablation ranges from 0.01 mJ to 5 mJ. The basic laser also includes a compact, argon fluoride excimer laser (at 193 nm) with repetition rate of (1-1,000) Hz, energy per pulse of (0.5-10) mJ, pulse duration of (1-50) nanoseconds and a compact, Er:YAG laser (at 2.94 microns) with repetition rate of (1-200) Hz, energy per pulse of (50-500) mJ, pulse duration of (50-400) nanoseconds and frequency-

converted IR lasers of diode laser, optically-pumped Alexandrite or Li:SAF lasers, where efficient nonlinear crystals (as shown in FIG. 2) may be used to convert the fundamental wavelength (770-880 nm) into its fourth-harmonic at the UV tunable wavelength of (193-220 nm) with energy of (0.01-5.0) mJ, repetition rate of (1-10,000) and pulse duration of (0.05-50) nanoseconds. Only two nonlinear crystals are needed in this case and overall efficiency is higher than that of the fifth harmonic generation which requires three nonlinear crystals. The basic laser may also include ultrashort pulsed lasers, such as a commercialized mode-locked Ti:sapphire laser or other solid-state laser, with wavelength ranges of (750-1100 nm), repetition rates of (0.01-100 MHz), energy per pulse of (0.01-100) microjoules, and pulse durations of (0.05-10) picoseconds where focused beam spot size of (0.05-0.5) mm is required to achieve the ablation threshold. When using an ultrashort pulse laser with very high peak power density (gigawatts range), the tissue ablation should be insensitive to laser wavelengths since the tissue ablation is assisted by the plasma-enhanced absorption with minimal tissue thermal damage. A focused spot size of (0.05-0.5) mm of the ultrashort pulsed lasers would be appropriate to achieve the tissue ablation and precise ablation profile is available by the scanning device proposed by the present invention. Without a scanning device, an ultrashort pulsed laser cannot be used in refractive surgery due to its energy level of less than 0.1 mJ and spot size smaller than 0.5 mm. The above-described lasers may also be frequency-converted into UV ranges of (190-220) nm suitable for photoablation.

The basic laser also includes a mid-IR (2.5-3.2 microns) laser generated from optical parametric oscillation (OPO) using a near-IR laser (such as Nd:YAG or Nd:YLF, flash-lamp or diode-pumped) as the pumping sources and KTP or BBO as the frequency conversion crystals. The OPO laser has advantages over the Q-switched Er:YAG laser, including higher repetition rate (10-5,000 Hz) and shorter pulse width (1-40 n.s.). These advantages provide faster surgical procedure and reduced thermal damage on the ablated corneal tissue. Typical energy per pulse of the OPO laser is (0.1-10) mJ. Greater detail on OPO was published by the inventor in Optical Communications, vol. 75, p. 315 (1990).

Still referring to FIG. 1, the scanning device 12 is synchronized with the laser repetition rate, where the computer software is capable of providing predetermined patterns according to a patient's corneal topography for the corrections of myopia, hyperopia and astigmatism. Astigmatic correction, in particular, is difficult to perform in prior art systems using a non-scanning diaphragm but can be easily achieved by the present invention using a scanning device. Furthermore, a multi-zone procedure for high diopter (6-15) changes can be performed by the computer program rather than that of the conventional mechanical iris.

The low-power laser systems described in the present invention can perform the procedures normally required in high-power lasers because a scanning device is used to assure the uniform corneal ablation by beam overlap and the ablation threshold is achievable by small spot size.

Referring to FIG. 2, a preferred embodiment for the basic laser 10 of FIG. 1 having a UV wavelength includes a diode-pumped Nd:YAG (or Nd:YLF) 25 having a fundamental wavelength of 1064 nm (or 1047 and 1053 nm) 26 and is focused by a lens 27 into a doubling crystal 28 (KTP, KNbO₃, LBO or BBO) to generate a green wavelength 30 at 532 nm (or 524 and 527 nm). The green beam 30 is further converted by a fourth harmonic crystal 31 (BBO) to generate a UV wavelength 32 at 266 nm (or 262-263 nm) which is

finally converted by a fifth harmonic crystal 33 to generate the UV wavelength 11 at 213 nm (or 209–211 nm). From a commercially available diode-pumped Nd:YLF laser 1 am able to achieve the UV (at 209–211 nm) energy of 0.01–2 mJ per pulse with average-power of 0.1 to 0.5 W. This energy level when focused into a spot size of (0.1–0.5) mm is sufficient to ablate the corneal tissue. This diode-pumped fifth-harmonic system provides the most compact refractive UV solid-state laser available today with the advantages of long lifetime, low maintenance, portability and absence of toxic gas in comparison with the excimer lasers currently used by other companies. Furthermore by using the fundamental wavelength at 1064 nm (or 1053 or 1047 nm) or their second-harmonic (at 532, 524, or 527 nm), intrastroma photokeratectomy procedure may be performed by focusing the beam into the intrastroma area of the cornea. The laser presented in the present invention provide a compact, portable and low-cost IPK laser and has an advantage over the lasers used by other companies where the systems are currently more than five times heavier and are more costly.

In FIG. 3, a commercially available Ho:YAG (or Er:glass) or diode laser 35 (either flash-lamp or laser-diode pumped) is coupled by a fiber optic waveguide 36 with core diameter of (100–600) microns to a scanning device 37, in which the fundamental beam 38 with a wavelength of 2.1 (or 1.54) or (1.9–2.5) microns which is collimated by a lens 40 and coupled to the scanning gavo 41 and focused by another lens 42 onto the beam splitters 43 and 44, and finally delivered to a target (such as a patient's cornea) 45. The IR (2.1 microns) laser beam 38 is collinear with the aiming beam 46 (visible He—Ne or diode laser) and the patent corneal center is also defined by a commercial slit-lamp microscope station 47. The above-described apparatus offers the unique feature of non-contact laser thermokeratoplasty for precise coagulation in both spherical and astigmatic corneal power corrections with scanning patterns predetermined by a computer software hereinafter discussed. The focusing lens 28 may be motorized for varying the focal point and thus varying the coagulation cone size for optimal results. In the prior art of fiber-tip contact system, the precision of the coagulation zone and patterns are limited by doctors manual operation which is a much slower procedure than the computer controlled scanning device described in the present invention. The requirement of replacing the fiber-tip after each operation is also a drawback of the prior art systems. The advantages of the present system includes: precision coagulation zone and spot size, flexible patterns for a variety of corrections, fast processing time and elimination of the need for fiber-tip replacement.

Still referring to FIG. 3, the basic laser 22 in accordance with the preferred embodiment of the present invention is a free-running or continuous-wave (CW) flash-lamp or diode-laser pumped Ho:YAG (at 2.1 microns) or Er:glass (at 1.54 microns), or IR diode laser (1.9–2.5 microns) with average power of 0.5–5 W, pulse duration of 200–2,000 microseconds (if free-running). In the present invention, the IR wavelengths of 1.54 and 2.1 and (1.9–2.5) microns are chosen due to their strong tissue absorption which is required in the photo-coagulation processes. Similar lasing media of Ho:Tm:YAG and Ho:Tm:Cr:YAG is also included in the preferred embodiments of the present invention. The CW diode laser (1.9–2.5 microns) may be scanned in a faster rate than that of the free-running lasers.

FIGS. 4A through 4B summarize the possible coagulation patterns suitable for both spherical and astigmatic corneal reshaping in the LTK procedures in a cornea 50. FIG. 4-A with coagulation zone (CZ) of 5 to 9 mm and spot number

(SN) of (8-16) provides hyperopic corrections of 1-6 diopters; FIG. 4-B has a coagulation zone of 1-3 mm suitable for myopic corrections; FIG. 4-C has radial coagulation zone and spot number of 16-32, suitable for spherical hyperopic correction; FIG. 4-D has a coagulation zone of 1-9 mm and spot number of 50-200, suitable for precise coagulation control to stabilize and reinforce the collagen shrinkage tension; FIG. 4-E is designed for astigmatic change, where the coagulation patterns are chosen according to the corneal topography. By using the computer-controlled scanning, these patterns may be easily generated and predetermined according to the measured corneal topography of each patient. A combination of these patterns illustrated in FIGS. 4-A to 4-E enables the treatment of patient's optical power correction in all aspects of myopia, hyperopia, astigmatism and their mixed vision disorder. Furthermore, laser parameters such as energy per pulse, spot size and scanning patterns also provide another degree of freedom for the laser thermokeratoplasty process which are not usually available in the prior art systems using the contact fiber-tip.

The appropriate parameters relating to FIG. 4A-B are: laser energy per pulse of 5-50 mJ for free-running mode (200-400 micro-second duration), beam spot size of (0.1-1) mm, laser repetition rate of 5-30 Hz, coagulation zone of (1-10) mm, spot number of 8-200 spots and fiber core diameter of 100-600 microns, for a flash-lamp-pumped system. Also disclosed is the use of a diode-pumped Ho:YAG, either in a pulse-mode or continuous-wave (CW) mode. For a CW mode laser, energy of 10-100 mW is sufficient for coagulation when spot size of 0.05-0.5 mm is employed. In the diode-pumped system in CW mode or with a high-repetition-rate 20-100 Hz, a fast scanning enables completion of the coagulation procedures within 2-20 seconds depending upon the coagulation zone and spot number required. Fast scanning also provides a uniform collagen shrinkage unlike that of the prior art system using a manually operated fiber-tip which normally takes 1 to 5 minutes to complete in a multiple coagulation zone and high spot number. It is difficult to use a manually operated fiber-tip to generate the precise patterns as illustrated in FIG. 4 which can be easily performed in the computer-controlled scanning device as disclosed in the present invention. The patient's eye motion and decentration is a problem for prior art systems, but it is not a critical factor in the fast scanning device described herein.

Referring to FIG. 5, a laser-assisted myopic keratomileusis (MKM) and hyperopic keratomileusis (HKM) can be performed either on the outer corneal surface 51 or on the inner surface 52 to reshape the resealed corneal tissue without materially effecting the Bowman's layer. The preferred lasers are described in FIG. 1 including the UV (193-220 nm) and IR (2.5-3.2 microns) lasers. The non-invasive laser-assisted procedure disclosed in the present invention has the advantages over the procedures of photorefractive keratectomy and laser thermokeratoplasty including being safer, more stable with a higher diopter change, and without materially affecting epithelium and Bowman's layer. In comparison with the conventional keratomileusis, the laser-assisted myopic keratomileusis and hyperopic keratomileusis do not require corneal freezing and can perform very high diopter change not available by radial keratotomy or photorefractive keratectomy. Laser-assisted corneal reshaping can also be employed for a donor cornea in the procedure currently performed by epikeratophakia. Details of conventional lamellar refractive surgery may be found in Leo D. Bores, *Refractive Eye Surgery* (Blackwell Scientific Pub., 1993), Chapter 10.

202507140000
00806014440060

FIGS. 6A through 6D shows a nearly flat-top beam profile achieved by overlapping a series of laser beams, where the degree of overlap, 50%–80%, depends on the individual beam profiles which are not required to be flat-top. In the present invention, the preferred individual beam profile is either a 70% Gaussian or a symmetric profile. In the laboratory, I have demonstrated a smooth laser-ablated PMMA surface with zone diameter of 3–6 mm by overlapping a large number of pulses, 500 to 5,000, each one having a spot size of 0.8–1.2 mm. Moreover smooth transition among the ablation zones were achieved without the transition zone steps found in prior art systems using mechanical diaphragms. In addition to the myopic and hyperopic scanning patterns of 6B and 6C, one of the significant features of the present scanning device is that it can generate predetermined patterns based upon the corneal topography for astigmatism correction (see 6D). Corneal scar may also be easily located by a topography and photoablated by a laser based on the computer-controlled scanning patterns. The preferred lasers for the procedures described in FIG. 6 are discussed in connection with FIG. 1.

Still referring to FIG. 6, the scanning schemes were tested by ablation on PMMA plastic. The computer software is based upon the mathematical model described earlier in equations 1 and 2 where the center ablation thickness was equally spaced to define the associated scanning diameters. Given the ablation thickness per pulse and per ablation layer (at a given scanning diameter), one may easily obtain the overall corneal surface ablation profile, (see equation (1)). The number of required ablation layers is therefore proportional to the diopter change (D) and square of the ablation zone (W). The computer parameters designed in the present invention include: diopter change (D), optical zone diameter (W), and the degrees of overlap in both tangential (TD) and radial (RD) direction of the scan patterns as shown in FIGS. 6A through 6D. Smooth PMMA surface ablation was achieved by optimization of laser spot size, energy and the overlap parameters of TD and RD. Experimental data indicates that larger overlap provides smoother surface ablation; however, longer ablation time is required for a given diopter change, laser energy and repetition rate (RR). Larger RR, 50–100 Hz, provides shorter ablation time which is typically in the range of (20–40) seconds for diopter changes of 2–8 in myopic treatment based upon my measurements. The prior art high-power excimer lasers with a typical RR of 5–15 Hz will be impossible to achieve the results described above even if they use the present scanning device.

Still referring to FIGS. 6, using the UV lasers (193, 210 and 213 nm) I have achieved ablation depths of (20–40) microns by overlapping (2000–4000) laser pulses, which give an ablation depth of 0.05–0.1 microns per pulse. The ablation depths are measured by 1 μ microsensor (made by Tencor Instruments) which has a resolution of about 0.5 microns or better. Ablation curves, ablation depth versus laser intensity, were obtained by varying the laser energy or the spot size. Given the ablation rate (ablation thickness per pulse), I am able to calibrate the number of pulses and the degree of beam overlap required to achieve the diopter change on the PMMA, where the diopters of the ablated PMMA are measured by the standard lensmeter. In vitro measurement of corneal tissue ablation can be calibrated according to the comparison of the ablation rate between PMMA and tissue. For myopic and hyperopic corrections, I have used circular scanning patterns with beam overlap controlled by the tangential scanning speed and diameters of the adjoined circles. The preferred scanning scheme is from small circle to large circle. For example, given a laser spot

6642359 "T 448060
002060" F 448060

size of 1 mm, a radial overlap of 50% will require the scanning circle to start from 1 mm diameter to 5 mm diameters with an increment of 0.5 mm for an optical zone of 5 mm. Furthermore, a tangential overlap of 50% requires the scanner to move at an angular speed of about 23 degrees within the interval between each laser pulse. In my computer-controlled scanning device, software was developed to synchronize the laser repetition rate with the scanning gavo to control the above-described overlap patterns. In addition to the circular patterns described for myopic and hyperopic treatments, a linear scanning pattern may also be used in particular for the myopic and astigmatic corrections.

It is important to note that a uniform individual beam profile and energy stability of the laser, under the present scanning device, are not critical in achieving an overall uniform ablation zone whereas they are very critical for prior art systems using expanding iris devices. Given the ablation rate per overlapped circle, the overall diopter correction may be achieved by the appropriate increment in diameters of the expanding circles. Greater details of beam scanning and overlapping will be further discussed in connection with FIGS. 9-11.

Referring to FIGS. 7A and 7B, a laser radial keratectomy (LRK) performed by laser excision has advantages over the conventional diamond-knife radial keratotomy (RK) including higher predictability and reproducibility by precise control of the excision (or ablation) depth. Furthermore, using the scanning device of the present invention, laser radial keratotomy may be performed easily and rapidly with less dependance upon the surgeon's skill and experience. Corneal reshaping may be performed by controlling the laser parameters such as spot size, intensity, scanning speed, beam overlap, and the excision depth per pulse which typically ranges from 0.2 to 0.5 microns. The excision depth precision of a laser is at least 10 times better than that of a knife. This "laser-knife" should be able to perform all the radial keratotomy procedures performed by a "diamond-knife" by using similar techniques to those introduced in the Book of Leo D. Botes, Refractive Eye Surgery, Chapters 8 and 9. Examples of laser radial keratotomy are shown in 7A for myopia (radial-cut) and 7B for astigmatism (T-cut). The preferred lasers for laser radial keratotomy include the lasers described in FIG. 1.

Referring to FIGS. 8A and 8D, the ablation patterns suitable for refractive procedures may be generated by using coated windows such as UV (or IR) grade fused silica, MgF, BaF or sapphire (when an IR laser is used), with preferred thickness of (0.5-2) mm and diameter of (8-15) mm. Referring to FIG. 8A, scanning laser beams 53 (at wavelength of UV or IR) with circular scanning pattern to deliver uniform (or constant) laser energy over the coated window 44 with coating specification (at UV or IR wavelength) according to the profile on the corneal tissue 55 (or PMMA surface) will also achieve the same pattern described by equation (1). FIGS. 8B and 8C show the reflection profiles of the coated windows for myopia, hyperopia and astigmatism, respectively, based on predetermined diopter changes. These coated windows disclosed in the present invention can be reused for cost effectiveness and has an advantage over the prior art system using the disposable mask which is costly and is difficult to provide reproducible results due to the non-uniform transmission or ablation properties of the mask.

Greater detail of the features of the present invention regarding beam overlap, scanning and orientation in order to achieve uniform ablation profiles to meet the clinical requirements of corneal reshaping are demonstrated as fol-

344,000,000 "T" 444,000,000
000,000,000 "F" 444,000,000

lows. The actually measured PMMA profiles were generated from the Microsensor (made by TENCOR INSTRUMENTS, INC.) using our ArF laser (the Compak-200 Mini-Excimer system, made by LaserSight, Inc.) having laser parameters of: (2-4 mJ) energy at the output window, operated at (50-200) Hz, with the beam focused onto the corneal surface at a spot size of about (0.2-1.2) mm, with energy per pulse of (0.5-1.5) mJ, tunable by a coated MgF window.

Referring to FIG. 9A, we show the schematic of the motion of the scanning beam with a spot size of 1 mm in this example. Beam overlap function(L) is defined by the beam displacement parameters of dx and dy (in x and y direction, respectively, on the corneal plane) adjustable by the computer controlled software, where $L_x = 1 - dx/R$ and $L_y = 1 - dy/R$, where R is the beam diameter. The degrees of smoothness (DS) of the ablated PMMA surface (a plastic sheet which has been commonly used for the calibration of UV laser ablation on corneal tissue) is governed by the degrees of overlap function $L = L_x + L_y$. Greater DS can be performed by using greater L, which, however, will also cause a slower procedure speed (v), at a given laser average-power(p), beam spot size(R) and energy per pulse (E). Desired procedure time of 20 to 50 seconds are typical for patient diopter corrections (myopic) of D=-3 to -10, where patient centration is conducted by a visible fixation light for the patient to look at without eye movement. Including some of the compensation from the recovered epithelium filling on the ablated corneal surface, the roughness of the corneal tissue, calibrated by the PMMA surface, should be within the range of (0.2-2) microns. Therefore, we are optimizing the parameters of dx, dy, L, p, E and R in order to achieve the above-described clinical requirements.

Referring to FIG. 9B, a comparison is shown to demonstrate the degrees of smoothness of the ablated PMMA at two sets of displacements: curve A (dx=dy=0.5 mm) and curve B (dx=0.5 mm, dy=0.3 mm). These PMMA profiles were generated from a Microsensor scanned along the y direction to show the difference in smoothness caused by the difference in dy values (at a fixed dx value). It is clearly demonstrated by comparing Curves A and B that a smoother surface is generated with a smaller displacement (dy=0.3 mm), or larger beam overlap $L_x = 70\%$. In this particular example, the basic beam profile is worse than a 50% Gaussian and actually has a three-lob structure which is typical in an ArF excimer laser. Even under this poor beam uniformity condition, we are still able to obtain very uniform overall ablated areas of (2-9) mm in diameter, as shown in FIG. 9B (curve B) with surface roughness less than 1 microns (vs. about 10 microns in curve A), when a set of appropriate beam overlap parameters are used. Smaller dx and dy will further improve smoothness, which, however, may take a longer operation time. As shown in above example (using dx=0.5 mm and dy=0.3 mm), only 30 seconds is needed for a D=-4 diopter correction with enough smoothness of the PMMA surface, where I used a pulse energy of 0.9 mJ (on the PMMA surface), with the system operated at 100 Hz in this example.

In addition to the overlap function, I have been able to further improve the beam uniformity by the beam orientation method as follows. As shown in FIG. 10A, I used linear scan patterns for multi-layer ablation on a PMMA sheet, where parameters of E=0.9 mJ, spot size of 1 mm, dx=dy=0.5 mm were used. In one case, I repeated the linear scan pattern along the x-direction, or rotation angle (A)=zero, for about 25 times (layers). To see the improvement due to pattern orientation, I tried the second case by rotating the

linear-scan angle (A) by about 65 degrees in each successive scan layers. An angle $A=65$ degrees was chosen in this particular example to randomize the basic beam structure (having a non-uniform profile) and to achieve the uniform overall ablation. This averaging procedure by beam orientation will largely reduce the potential roughness caused by the basic beam structure, noting that rotation angles, such as 20, 30, 60 or 120 degrees (in which 360 degrees can be divided into integers), should be avoided to prevent repeated patterns after a few rotation layers. A larger angle (A) is chosen for smaller diopter corrections and vice versa for the best results. This is to make sure that enough beam randomization is performed for various diopter corrections which are proportional to the numbers of scanned layers. Comparisons are shown in FIG. 10B for $A=0$ (nonrotated case, curve A) and for $A=65$ (rotated case, curve B), where $dx=dy=0.5$ mm were used in both cases. Significant smoothness of ablated PMMA was achieved in the rotated case (curve B) even when a large displacement of $dy=0.5$ mm was used, compared to curve B in FIG. 10B and curve A in FIG. 9B. The larger displacement, or smaller overlap results in a faster procedure, however, this results in a loss of smoothness if beam rotation is not used. Using the above-described techniques, I am able to generate the predetermined ablation profiles corresponding to various refractive corrections such as myopic, hyperopic and astigmatic with clinically acceptable tissue smoothness and procedures times requirement.

Referring to FIG. 11, an example for myopic correction is shown. FIG. 11A shows the schematic of rotated ablated areas with increasing diameters (from about 0.5 to 6 mm) governed by Equation (1), where a typical number of layers (or scanned areas at various diameters) of 25 is needed for a -5 diopter correction. For an optical zone of 5 mm, this represents an ablation rate of about 2 microns in corneal tissue in each layer, where a pulse energy of about 0.9 mJ at spot size of 1 mm and repetition rate of 100 Hz is used. For smaller diopter corrections, a smaller energy (0.6-0.8 mJ), or smaller ablation rate (0.5-1.0 microns) is desired for smoother and more accurate results. Moreover, a smaller spot size of (0.1-0.5 mm) may be used for better control of the ablation profile (with greater accuracy), but a faster laser repetition rate larger than 500 Hz would be required for a reasonable procedure speed of (20-50) seconds to cover (-3 to -10) diopter corrections. In this situation the diode pumped UV solid state laser described earlier will be a better candidate than the Excimer laser. FIG. 11B shows the PMMA ablation profile measured from a Microsensor using the techniques shown in FIG. 11A, where an ablation zone size of about 5 mm with center depth of about 16 microns were shown. I believe that the PMMA profiles shown in FIGS. 9 through 11 represent, for the first time, the novel features of the techniques disclosed in the present invention. Some of the prior art has never demonstrated the actual ablation data, although a simple concept of beam scanning has been proposed. The comparisons in FIGS. 9 and 10 have demonstrated that the prior techniques as set forth in the background hereto would never achieve the smooth surface as shown here. In addition, given the laser parameters proposed in the present invention of low-energy (2-4 mJ) with nonuniform basic beam profile and without using mechanical beam re-shaping, it is impossible for the prior art to achieve clinically meaningful results. A high-power laser of 100-300 mJ with a complex means of beam uniformity is always required in the prior art patents.

The method disclosed in the present invention combines beam scanning, overlapping and pattern rotation (random-

5

14

2

3

1

●

6

3. A method of performing corneal refractive surgery by reshaping a portion of the corneal surface in accordance with claim 1 in which the step of selecting a laser includes selecting a flash lamp pumped UV laser having an output wavelength between 193 and 220 nanometers, and energy per pulse of 0.1 to 10 mJ/pulse, a repetition rate of between 1 Hz and 10 KHz, and a pulse duration between 0.1 picoseconds to 50 nanoseconds and a focused spot size of (0.05–1.5) mm on the corneal surface.

5. A method of performing corneal refractive surgery by reshaping a portion of the corneal surface in accordance with claim 1 in which the step of selecting a laser includes selecting a free-running Ho:YAG laser having an output wavelength of about 2.1 microns at an average power of between 0.5-5 watts and a focused generally fixed spot size of between 0.1-1 mm.

6. A method of performing corneal refractive surgery by reshaping a portion of the corneal surface in accordance with claim 1 in which the step of selecting a laser includes selecting a free-running Er:glass laser having an output wavelength of about 1.54 microns at an average power of between 0.5-5 watts with a focused generally fixed spot size of between 0.1-1 mm.

7. A method of performing corneal refractive surgery by 35
reshaping a portion of the corneal surface in accordance with
claim 1 in which the step of selecting a laser includes
selecting a free-running Er:glass laser having an output
wavelength of between 1.9 to 2.5 microns at a power of
between 0.5-5 watts and a focused generally fixed spot size 40
of between 0.1-1 mm.

8. A method of performing corneal refractive surgery by reshaping a portion of the corneal surface in accordance with claim 1 in which the step of selecting a laser includes selecting a Q-switched Er:YAG laser having an output wavelength of 2.94 microns, and a pulse duration of between 50 to 400 nanoseconds, with an energy per pulse of between 50-500 mJ and a repetition rate of between 1 and 200 Hz with a focused generally fixed spot size of between 0.2-2 mm.

9. A method of performing corneal refractive surgery by reshaping a portion of the corneal surface in accordance with claim 1 in which the step of selecting a laser includes selecting an ultra-short pulsed laser having an output wavelength of between 750 to 1100 nanometers, energy per pulse of between 0.01 to 100 microjoules, and a repetition rate of between 0.01 to 100 MHz, and pulse duration of between 0.05–10 picoseconds and a focused generally fixed spot size of between 0.05–0.5 mm.

10. A method of performing corneal refractive surgery by reshaping a portion of the corneal surface in accordance with claim 1 in which the step of selecting a laser includes selecting an OPO mid-IR laser having an output of 2.5-3.2 microns, a pulse duration of between 1-40 nanoseconds and energy per pulse of between 0.1 to 10 mJ, and a repetition rate of between 10 and 5,000 Hz and a focused generally fixed spot size on the corneal surface of between 0.1-2 mm.

5

10

15

2

3

3

1

•

21. A method of performing corneal refractive surgery by reshaping a portion of the corneal surface in accordance with

claim 18 in which the step of scanning includes scanning through a coated window made of materials highly transparent to an IR laser having an output beam of (2.5-3.2) microns.

22. A method of performing corneal refractive surgery by reshaping a portion of the corneal surface in accordance with claim 1 in which the step of controlling said scanning mechanism includes controlling said scanning which has a

5

11-12-13-14-15-16-17-18-19-20-21-22-23-24-25-26-27-28-29-30-31-32-33-34-35-36-37-38-39-40-41-42-43-44-45-46-47-48-49-50-51-52-53-54-55-56-57-58-59-60-61-62-63-64-65-66-67-68-69-70-71-72-73-74-75-76-77-78-79-80-81-82-83-84-85-86-87-88-89-90-91-92-93-94-95-96-97-98-99-100-101-102-103-104-105-106-107-108-109-110-111-112-113-114-115-116-117-118-119-120-121-122-123-124-125-126-127-128-129-130-131-132-133-134-135-136-137-138-139-140-141-142-143-144-145-146-147-148-149-150-151-152-153-154-155-156-157-158-159-160-161-162-163-164-165-166-167-168-169-170-171-172-173-174-175-176-177-178-179-180-181-182-183-184-185-186-187-188-189-190-191-192-193-194-195-196-197-198-199-200-201-202-203-204-205-206-207-208-209-210-211-212-213-214-215-216-217-218-219-220-221-222-223-224-225-226-227-228-229-230-231-232-233-234-235-236-237-238-239-240-241-242-243-244-245-246-247-248-249-250-251-252-253-254-255-256-257-258-259-260-261-262-263-264-265-266-267-268-269-270-271-272-273-274-275-276-277-278-279-280-281-282-283-284-285-286-287-288-289-290-291-292-293-294-295-296-297-298-299-300-301-302-303-304-305-306-307-308-309-310-311-312-313-314-315-316-317-318-319-320-321-322-323-324-325-326-327-328-329-330-331-332-333-334-335-336-337-338-339-340-341-342-343-344-345-346-347-348-349-350-351-352-353-354-355-356-357-358-359-360-361-362-363-364-365-366-367-368-369-370-371-372-373-374-375-376-377-378-379-380-381-382-383-384-385-386-387-388-389-390-391-392-393-394-395-396-397-398-399-400-401-402-403-404-405-406-407-408-409-410-411-412-413-414-415-416-417-418-419-420-421-422-423-424-425-426-427-428-429-430-431-432-433-434-435-436-437-438-439-440-441-442-443-444-445-446-447-448-449-450-451-452-453-454-455-456-457-458-459-460-461-462-463-464-465-466-467-468-469-470-471-472-473-474-475-476-477-478-479-480-481-482-483-484-485-486-487-488-489-490-491-492-493-494-495-496-497-498-499-500-501-502-503-504-505-506-507-508-509-510-511-512-513-514-515-516-517-518-519-520-521-522-523-524-525-526-527-528-529-530-531-532-533-534-535-536-537-538-539-540-541-542-543-544-545-546-547-548-549-550-551-552-553-554-555-556-557-558-559-560-561-562-563-564-565-566-567-568-569-570-571-572-573-574-575-576-577-578-579-580-581-582-583-584-585-586-587-588-589-590-591-592-593-594-595-596-597-598-599-600-601-602-603-604-605-606-607-608-609-610-611-612-613-614-615-616-617-618-619-620-621-622-623-624-625-626-627-628-629-630-631-632-633-634-635-636-637-638-639-640-641-642-643-644-645-646-647-648-649-650-651-652-653-654-655-656-657-658-659-660-661-662-663-664-665-666-667-668-669-670-671-672-673-674-675-676-677-678-679-680-681-682-683-684-685-686-687-688-689-690-691-692-693-694-695-696-697-698-699-700-701-702-703-704-705-706-707-708-709-710-711-712-713-714-715-716-717-718-719-720-721-722-723-724-725-726-727-728-729-730-731-732-733-734-735-736-737-738-739-740-741-742-743-744-745-746-747-748-749-750-751-752-753-754-755-756-757-758-759-760-761-762-763-764-765-766-767-768-769-770-771-772-773-774-775-776-777-778-779-780-781-782-783-784-785-786-787-788-789-790-791-792-793-794-795-796-797-798-799-800-801-802-803-804-805-806-807-808-809-810-811-812-813-814-815-816-817-818-819-820-821-822-823-824-825-826-827-828-829-830-831-832-833-834-835-836-837-838-839-840-841-842-843-844-845-846-847-848-849-850-851-852-853-854-855-856-857-858-859-860-861-862-863-864-865-866-867-868-869-870-871-872-873-874-875-876-877-878-879-880-881-882-883-884-885-886-887-888-889-890-891-892-893-894-895-896-897-898-899-900-901-902-903-904-905-906-907-908-909-910-911-912-913-914-915-916-917-918-919-920-921-922-923-924-925-926-927-928-929-930-931-932-933-934-935-936-937-938-939-940-941-942-943-944-945-946-947-948-949-950-951-952-953-954-955-956-957-958-959-960-961-962-963-964-965-966-967-968-969-970-971-972-973-974-975-976-977-978-979-980-981-982-983-984-985-986-987-988-989-990-991-992-993-994-995-996-997-998-999-1000-1001-1002-1003-1004-1005-1006-1007-1008-1009-1010-1011-1012-1013-1014-1015-1016-1017-1018-1019-1020-1021-1022-1023-1024-1025-1026-1027-1028-1029-1030-1031-1032-1033-1034-1035-1036-1037-1038-1039-1040-1041-1042-1043-1044-1045-1046-1047-1048-1049-1050-1051-1052-1053-1054-1055-1056-1057-1058-1059-1060-1061-1062-1063-1064-1065-1066-1067-1068-1069-1070-1071-1072-1073-1074-1075-1076-1077-1078-1079-1080-1081-1082-1083-1084-1085-1086-1087-1088-1089-1090-1091-1092-1093-1094-1095-1096-1097-1098-1099-1100-1101-1102-1103-1104-1105-1106-1107-1108-1109-1110-1111-1112-1113-1114-1115-1116-1117-1118-1119-1120-1121-1122-1123-1124-1125-1126-1127-1128-1129-1130-1131-1132-1133-1134-1135-1136-1137-1138-1139-1140-1141-1142-1143-1144-1145-1146-1147-1148-1149-1150-1151-1152-1153-1154-1155-1156-1157-1158-1159-1160-1161-1162-1163-1164-1165-1166-1167-1168-1169-1170-1171-1172-1173-1174-1175-1176-1177-1178-1179-1180-1181-1182-1183-1184-1185-1186-1187-1188-1189-1190-1191-1192-1193-1194-1195-1196-1197-1198-1199-1200-1201-1202-1203-1204-1205-1206-1207-1208-1209-1210-1211-1212-1213-1214-1215-1216-1217-1218-1219-1220-1221-1222-1223-1224-1225-1226-1227-1228-1229-1230-1231-1232-1233-1234-1235-1236-1237-1238-1239-1240-1241-1242-1243-1244-1245-1246-1247-1248-1249-1250-1251-1252-1253-1254-1255-1256-1257-1258-1259-1260-1261-1262-1263-1264-1265-1266-1267-1268-1269-1270-1271-1272-1273-1274-1275-1276-1277-1278-1279-1280-1281-1282-1283-1284-1285-1286-1287-1288-1289-1290-1291-1292-1293-1294-1295-1296-1297-1298-1299-1300-1301-1302-1303-1304-1305-1306-1307-1308-1309-1310-1311-1312-1313-1314-1315-1316-1317-1318-1319-1320-1321-1322-1323-1324-1325-1326-1327-1328-1329-1330-1331-1332-1333-1334-1335-1336-1337-1338-1339-1340-1341-1342-1343-1344-1345-1346-1347-1348-1349-1350-1351-1352-1353-1354-1355-1356-1357-1358-1359-1360-1361-1362-1363-1364-1365-1366-1367-1368-1369-1370-1371-1372-1373-1374-1375-1376-1377-1378-1379-1380-1381-1382-1383-1384-1385-1386-1387-1388-1389-1390-1391-1392-1393-1394-1395-1396-1397-1398-1399-1400-1401-1402-1403-1404-1405-1406-1407-1408-1409-1410-1411-1412-1413-1414-1415-1416-1417-1418-1419-1420-1421-1422-1423-1424-1425-1426-1427-1428-1429-1430-1431-1432-1433-1434-1435-1436-1437-1438-1439-1440-1441-1442-1443-1444-1445-1446-1447-1448-1449-1450-1451-1452-1453-1454-1455-1456-1457-1458-1459-1460-1461-1462-1463-1464-1465-1466-1467-1468-1469-1470-1471-1472-1473-1474-1475-1476-1477-1478-1479-1480-1481-1482-1483-1484-1485-1486-1487-1488-1489-1490-1491-1492-1493-1494-1495-1496-1497-1498-1499-1500-1501-1502-1503-1504-1505-1506-1507-1508-1509-1510-1511-1512-1513-1514-1515-1516-1517-1518-1519-1520-1521-1522-1523-1524-1525-1526-1527-1528-1529-1530-1531-1532-1533-1534-1535-1536-1537-1538-1539-1540-1541-1542-1543-1544-1545-1546-1547-1548-1549-1550-1551-1552-1553-1554-1555-1556-1557-1558-1559-1560-1561-1562-1563-1564-1565-1566-1567-1568-1569-1570-1571-1572-1573-1574-1575-1576-1577-1578-1579-1580-1581-1582-1583-1584-1585-1586-1587-1588-1589-1590-1591-1592-1593-1594-1595-1596-1597-1598-1599-1600-1601-1602-1603-1604-1605-1606-1607-1608-1609-1610-1611-1612-1613-1614-1615-1616-1617-1618-1619-1620-1621-1622-1623-1624-1625-1626-1627-1628-1629-1630-1631-1632-1633-1634-1635-1636-1637-1638-1639-1640-1641-1642-1643-1644-1645-1646-1647-1648-1649-1650-1651-1652-1653-1654-1655-1656-1657-1658-1659-1660-1661-1662-1663-1664-1665-1666-1667-1668-1669-1670-1671-1672-1673-1674-1675-1676-1677-1678-1679-1680-1681-1682-1683-1684-1685-1686-1687-1688-1689-1690-1691-1692-1693-1694-1695-1696-1697-1698-1699-1700-1701-1702-1703-1704-1705-1706-1707-1708-1709-1710-1711-1712-1713-1714-1715-1716-1717-1718-1719-1720-1721-1722-1723-1724-1725-1726-1727-1728-1729-1730-1731-1732-1733-1734-1735-1736-1737-1738-1739-1740-1741-1742-1743-1744-1745-1746-1747-1748-1749-1750-1751-1752-1753-1754-1755-1756-1757-1758-1759-1760-1761-1762-1763-1764-1765-1766-1767-1768-1769-1770-1771-1772-1773-1774-1775-1776-1777-1778-1779-1780-1781-1782-1783-1784-1785-1786-1787-1788-1789-1790-1791-1792-1793-1794-1795-1796-1797-1798-1799-1800-1801-1802-1803-1804-1805-1806-1807-1808-1809-1810-1811-1812-1813-1814-1815-1816-1817-1818-1819-1820-1821-1822-1823-1824-1825-1826-1827-1828-1829-1830-1831-1832-1833-1834-1835-1836-1837-1838-1839-1840-1841-1842-1843-1844-1845-1846-1847-1848-1849-1850-1851-1852-1853-1854-1855-1856-1857-1858-1859-1860-1861-1862-1863-1864-1865-1866-1867-1868-1869-1870-1871-1872-1873-1874-1875-1876-1877-1878-1879-1880-1881-1882-1883-1884-1885-1886-1887-1888-1889-1890-1891-1892-1893-1894-1895-1896-1897-1898-1899-1900-1901-1902-1903-1904-1905-1906-1907-1908-1909-1910-1911-1912-1913-1914-1915-1916-1917-1918-1919-1920-1921-1922-1923-1924-1925-1926-1927-1928-1929-1930-1931-1932-1933-1934-1935-1936-1937-1938-1939-1940-1941-1942-1943-1944-1945-1946-1947-1948-1949-1950-1951-1952-1953-1954-1955-1956-1957-1958-1959-1960-1961-1962-1963-1964-1965-1966-1967-1968-1969-1970-1971-1972-1973-1974-1975-1976-1977-1978-1979-1980-1981-1982-1983-1984-1985-1986-1987-1988-1989-1990-1991-1992-1993-1994-1995-1996-1997-1998-1999-2000-2001-2002-2003-2004-2005-2006-2007-2008-2009-2010-2011-2012-2013-2014-2015-2016-2017-2018-2019-2020-2021-2022-2023-2024-2025-2026-2027-2028-2029-2030-2031-2032-2033-2034-2035-2036-2037-2038-2039-2040-2041-2042-2043-2044-2045-2046-2047-2048-2049-2050-2051-2052-2053-2054-2055-2056-2057-2058-2059-2060-2061-2062-2063-2064-2065-2066-2067-2068-2069-2070-2071-2072-2073-2074-2075-2076-2077-2078-2079-2080-2081-2082-2083-2084-2085-2086-2087-2088-2089-2090-2091-2092-2093-2094-2095-2096-2097-2098-2099-2100-2101-2102-2103-2104-2105-2106-2107-2108-2109-2110-2111-2112-2113-2114-2115-2116-2117-2118-2119-2120-2121-2122-2123-2124-2125-2126-2127-2128-2129-2130-2131-2132-2133-2134-2135-2136-2137-2138-2139-2140-2141-2142-2143-2144-2145-2146-2147-2148-2149-2150-2151-2152-2153-2154-2155-2156-2157-2158-2159-2160-2161-2162-2163-2164-2165-2166-2167-2168-2169-2170-2171-2172-2173-2174-2175-2176-2177-2178-2179-2180-2181-2182-2183-2184-2185-2186-2187-2188-2189-2190-2191-2192-2193-2194-2195-2196-2197-2198-2199-2200-2201-2202-2203-2204-2205-2206-2207-2208-2209-2210-2211-2212-2213-2214-2215-2216-2217-2218-2219-2220-2221-2222-2223-2224-2225-2226-2227-2228-2229-2230-2231-2232-2233-2234-2235-2236-2237-2238-2239-2240-2241-2242-2243-2244-2245-2246-2247-2248-2249-2250-2251-2252-2253-2254-2255-2256-2257-2258-2259-2260-2261-2262-2263-2264-2265-2266-2267-2268-2269-2270-2271-2272-2273-2274-2275-2276-2277-2278-2279-2280-2281-2282-2283-2284-2285-2286-2287-2288-2289-2290-2291-2292-2293-2294-2295-2296-2297-2298-2299-2300-2301-2302-2303-2304-2305-2306-2307-2308-2309-2310-2311-2312-2313-2314-2315-2316-2317-2318-2319-2320-2321-2322-2323-2324-2325-2326-2327-2328-2329-2330-2331-2332-2333-2334-2335-2336-2337-2338-2339-2340-2341-2342-2343-2344-2345-2346-2347-2348-2349-2350-2351-2352-2353-2354-2355-2356-2357-2358-2359-2360-2361-2362-2363-2364-2365-2366-2367-2368-2369-2370-2371-2372-2373-2374-2375-2376-2377-2378-2379-2380-2381-2382-2383-2384-2385-2386-2387-2388-2389-2390-2391-2392-2393-2394-2395-2396-2397-2398-2399-2400-2401-2402-2403-2404-2405-2406-2407-2408-2409-2410-2411-2412-2413-2414-2415-2416-2417-2418-2419-2420-2421-2422-2423-2424-2425-2426-2427-2428-2429-2430-2431-2432-2433-2434-2435-2436-2437-2438-2439-2440-2441-2442-2443-2444-2445-2446-2447-2448-2449-2450-2451-2452-2453-2454-2455-2456-2457-2458-2459-2460-2461-2462-2463-2464-2465-2466-2467-2468-2469-2470-2471-2472-2473-2474-2475-2476-2477-2478-2479-2480-2481-2482-2483-2484-2485-2486-2487-2488-2489-2490-2491-2492-2493-2494-2495-2496-2497-2498-2499-2500-2501-2502-2503-2504-2505-2506-2507-2508-2509-2510-2511-2512-2513-2514-2515-2516-2517-2518-2519-2520-2521-2522-2523-2524-2525-2526-2527-2528-2529-2530-2531-2532-2533-2534-2535-2536-2537-2538-2539-2540-2541-2542-2543-2544-2545-2546-2547-2548-2549-2550-2551-2552-2553-2554-2555-2556-2557-2558-2559-2560-2561-2562-2563-2564-2565-2566-2567-2568-2569-2570-2571-2572-2573-2574-2575-2576-2577-2578-2579-2580-2581-2582-2583-2584-2585-2586-2587-2588-2589-2590-2591-2592-2593-2594-2595-2596-2597-2598-2599-2600-2601-2602-2603-2604-2605-2606-2607-2608-2609-2610-2611-2612-2613-2614-2615-2616-2617-2618-2619-2620-2621-2622-2623-2624-2625-2626-2627-2628-2629-2630-2631-2632-2633-2634-2635-2636-2637-2638-2639-2640-2641-2642-2643-2644-2645-2646-2647-2648-2649-2650-2651-2652-2653-2654-

23. A method of performing corneal refractive surgery by reshaping a portion of the corneal surface in accordance with claim 1 including the step of scanning in a uniform scanned pattern with a spatial overlap of 50-80% and beam orientation whereby the initial beam profile uniformity is not critical.

* * * * *

[illegible]

24. A method for performing ophthalmic surgery, comprising:
pulsing a laser beam at a repetition rate of at least 20 Hz;

and scanning said pulsed laser beam in a substantially overlapping pattern on said corneal tissue.

25. The method for performing ophthalmic surgery according to claim 24, wherein:
said laser beam provides an energy level of no greater than 10 mJ per pulse to said corneal tissue.

26. The method for performing ophthalmic surgery according to claim 24, wherein:
said laser beam provides an energy level of no greater than 20 mJ per pulse to said corneal tissue.

27. The method for performing ophthalmic surgery according to claim 24, wherein:
said laser beam provides an energy level of no greater than 50 mJ per pulse to said corneal tissue.

28. The method for performing ophthalmic surgery according to claim 24, wherein
said laser beam has a spot size on said corneal tissue of no greater than 1 mm.

29. The method for performing ophthalmic surgery according to claim 25, wherein:
said laser beam has a spot size on said corneal tissue of no greater than 1 mm.

30. The method for performing ophthalmic surgery according to claim 26, wherein:
said laser beam has a spot size on said corneal tissue of no greater than 1 mm.

31. The method for performing ophthalmic surgery according to claim 27, wherein:
said laser beam has a spot size on said corneal tissue of no greater than 1 mm.

32. The method for performing ophthalmic surgery according to claim 24, wherein:
successive pulses of said laser beam are overlapped at least 50 percent.

33. The method for performing ophthalmic surgery according to claim 24, wherein:
said laser beam is pulsed at a repetition rate

Figure 1 shows the typical \log_{10} of the concentration of the monomer, $\log_{10} M$, as a function of time, t , for the polymerization of α -methylstyrene initiated by BuLi in THF at -78°C . The concentration of the monomer decreases linearly with time, indicating a first-order reaction. The rate of polymerization is determined by the slope of the line, which is -0.0015 min^{-1} . The initial concentration of the monomer is $1.0 \times 10^{-2} \text{ M}$. The concentration of the initiator, BuLi , is $1.0 \times 10^{-3} \text{ M}$. The reaction is carried out in THF at -78°C . The data points are shown as open circles, and the line is a linear fit to the data.

of at least 50 Hz.

~~34. The method for performing ophthalmic surgery according to claim 25, wherein:~~

5 ~~said laser beam is pulsed at a repetition rate~~
of at least 50 Hz.

35. The method for performing ophthalmic surgery according to claim 24, wherein:

10 ~~said pulsed laser beam is scanned~~
synchronously with said pulses of said laser beam.

36. The method for performing ophthalmic surgery
according to claim 24, wherein:

15 an area of corneal tissue in a range of 0.05
to 0.5 microns deep is removed with each pulse of
said laser beam.

37. The method for performing ophthalmic surgery
according to claim 24, wherein:

said pulsed laser beam is scanned in circular
patterns.

38. The method for performing ophthalmic surgery according to claim 24, wherein:

said pulsed laser beam is scanned in linear patterns.

SUB ~~A2~~
133 30

39. A method for performing ophthalmic surgery,
comprising:

~~pulsing a laser beam at an energy level of no greater than 20 mJ per pulse onto corneal tissue; and scanning said pulsed laser beam in a substantially overlapping pattern on said corneal tissue.~~

40. The method for performing ophthalmic surgery according to claim 39, wherein:

40 said laser beam has a spot size on said
corneal tissue of no greater than 1 mm.

~~41. The method for performing ophthalmic surgery according to claim 39, wherein:~~

45 successive pulses of said laser beam are
overlapped at least 50 percent.

42. The method for performing ophthalmic surgery according to claim 39, wherein:

50 said laser beam is pulsed at a repetition rate
of at least 20 Hz.

43. The method for performing ophthalmic surgery according to claim 39, wherein:
said laser beam is pulsed at a repetition rate of at least 50 Hz.

44. ~~The method for performing ophthalmic surgery according to claim 39, wherein:
said pulsed laser beam is scanned synchronously with said pulses of said laser beam.~~

45. The method for performing ophthalmic surgery according to claim 39, wherein:
an area of corneal tissue in a range of 0.05 to 0.5 microns deep is removed with each pulse of said laser beam.

46. The method for performing ophthalmic surgery according to claim 39, wherein:
said pulsed laser beam is scanned in circular patterns.

47. The method for performing ophthalmic surgery according to claim 39, wherein:
said pulsed laser beam is scanned in linear patterns.

48. A method of performing laser ablation on tissue, said method comprising:
providing a laser having a pulsed output beam of ultraviolet wavelength;
providing a galvanometer scanner; and
controlling said pulsed output beam with said galvanometer scanner to provide a substantially overlapping random pattern of beam pulses on said tissue.

49. ~~The method of performing laser ablation on tissue according to claim 48, wherein:
said pulsed output beam has an energy level of no greater than 10 mJ per pulse.~~

50. The method of performing laser ablation on tissue according to claim 48, wherein:
said pulsed output beam has an energy level
of less than 20 mJ per pulse.

51. The method of performing laser ablation on tissue according to claim 48, wherein:
a pulse repetition rate of said pulsed output beam is in a range of 50 to 100 Hz.

52. The method of performing laser ablation on

tissue according to claim 48, wherein:
said laser is selected to be a diode-pumped laser.

5 53. The method of performing laser ablation on
tissue according to claim 48, wherein:
said ultraviolet wavelength is in a range of
193 to 215 nm.

10 54. The method of performing laser ablation on
tissue according to claim 48, wherein:
said ultraviolet wavelength is 193 nm.

15 55. The method of performing laser ablation on
tissue according to claim 48, wherein:
said pulsed output beam has an energy level
in a range of 0.05 to 10 mJ per pulse.

SUB A4
B5

20 56. The method of performing laser ablation on
tissue according to claim 48, wherein:
said pulsed output beam has an energy level
of no greater than 50 mJ per pulse.

25 57. The method of performing laser ablation on
tissue according to claim 48, wherein:
said pulsed output beam has a spot size on
said tissue of no greater than 1 mm.

30 58. The method of performing laser ablation on
tissue according to claim 55, wherein:
said pulsed output beam has a spot size on
said tissue of no greater than 1 mm.

Pub B6

35 59. The method of performing laser ablation on
tissue according to claim 56, wherein:
said pulsed output beam has a spot size on
said tissue of no greater than 1 mm.

40 60. The method of performing laser ablation on
tissue according to claim 48, wherein:
successive pulses of said pulsed output
beam are overlapped at least 50 percent.

SUB A5
B7

45 61. The method of performing laser ablation on
tissue according to claim 48, wherein:
said pulsed output beam is pulsed at a
repetition rate of at least 20 Hz.

50 62. The method of performing laser ablation on
tissue according to claim 48, wherein:
said pulsed output beam is pulsed at a
repetition rate of at least 50 Hz.

synchronously with said pulses of said pulsed output beam.

an area of corneal tissue in a range of 0.05 to 0.5 microns deep is removed with each pulse of said pulsed output beam.

said pulsed output beam is scanned in circular patterns.

said pulsed output beam is scanned in linear patterns.

said pulsed output beam is scanned in concentric circles.

said concentric circles have increasing diameters.

~~a scanner constructed and arranged to control said pulsed beam into a substantially overlapping random pattern of beam pulses on said tissue.~~

said repetition rate is at least 50Hz.

said pulsed output beam has an energy level no greater than 10 mJ per pulse.

said scanner is constructed and arranged to

73. The apparatus for ablating tissue according to claim 69, wherein:

74. The apparatus for ablating tissue according to claim 69, wherein:

75. The apparatus for ablating tissue according to claim 69, wherein:

SUB ¹⁵ A ~~7~~ ~~7~~
B10

20 a laser adapted to emit a pulsed laser beam
of less than 20 mJ per pulse onto said corneal
surface; and

25 laser beam on said corneal surface to achieve a
smooth ablation of corneal tissue.

30 corneal surface according to claim 76, wherein:
said smooth ablation results in a surface
roughness of less than 1 micron.

35 surgery by reshaping a portion of a corneal surface,
said method comprising:
substantially overlapping a plurality of
ultraviolet laser beam pulses over an area of a corneal
surface sufficient to ablate a depth in a range of 0.05
40 and 0.5 microns of corneal tissue per ultraviolet laser
beam pulse;

said laser beam pulses having a pulse repetition rate of at least 50 pulses per second.

50 said laser beam pulses have an energy level
of no greater than 10 mJ per pulse.

80 The method of performing corneal refractive

[illegible]

surgery by reshaping a portion of a corneal surface according to claim 79, further comprising:
selecting a scanner to scan said overlapping plurality of laser beam pulses, said scanner deflecting said laser beam pulses a predetermined angle.

81. The method of performing corneal refractive surgery by reshaping a portion of a corneal surface according to claim 80, wherein:
said selected scanner is a galvanometer scanner.

SUB A8
B11
82. An ophthalmic surgery apparatus, comprising:
a laser adapted to emit a pulsed beam of less than 20 mJ per pulse; and
a computer-controlled scanning device coupled to said laser such that pulses of said beam are substantially overlapped to achieve a smooth ablation of corneal tissue.

83. The ophthalmic surgery apparatus according to claim 82, wherein:
said pulses are overlapped in a range of 50 to 80 percent.

SUB A9
B12
84. The ophthalmic surgery apparatus according to claim 82, wherein:
said laser is adapted to emit a pulsed beam of no greater than 10 mJ per pulse.

85. The ophthalmic surgery apparatus according to claim 82, wherein:
said pulsed beam has a spot size on said corneal tissue of less than or equal to 2 mm.

SUB A10
B13
86. The ophthalmic surgery apparatus according to claim 82, wherein:
said laser has a repetition rate in a range of 50 and 50,000 Hz.

87. The ophthalmic surgery apparatus according to claim 82, wherein said scanning device comprises:
a galvanometer.

88. The ophthalmic surgery apparatus according to claim 87, wherein:
said repetition rate of said laser is synchronized with said galvanometer.

89. The ophthalmic surgery apparatus according to claim 82, wherein:
successive pulses of said pulsed beam are rotated through a linear-scan angle by said scanning

SUB AH
BK

device.

90. A method of performing corneal refractive surgery by reshaping a portion of a corneal surface comprising:

selecting a laser having a pulsed output beam of ultraviolet wavelength and having an energy level less than 10 mJ/pulse;

selecting a scanning mechanism for scanning said laser output beam, said scanning mechanism including a galvanometer scanning mechanism for controlling said laser beam into an overlapping pattern of adjacent pulses;

coupling said laser beam to said scanning mechanism for scanning said laser beam over a predetermined surface;

focusing said scanning laser beam onto a corneal surface;

controlling said scanning mechanism to deliver the scanning laser beam in an overlapping pattern onto a plurality of positions on the corneal surface to photoablate or photocoagulate corneal tissue; and

removing from 0.05 to 0.5 microns of corneal tissue per pulse overlapped to remove tissue to a desired depth, whereby a patient's vision is corrected by the reshaping of the corneal surface of the patient's eye using a low power laser.

91. A method for performing ophthalmic surgery, comprising:

pulsing an ultraviolet laser beam; applying said pulsing ultraviolet laser beam onto corneal tissue; and

scanning said pulsing laser beam in a purposefully substantial overlapping pattern on said corneal tissue.

92. The method of performing ophthalmic surgery according to claim 91, wherein:

said pulsing ultraviolet laser beam is pulsed at a repetition rate of at least 20 Hz.

93. The method of performing ophthalmic surgery according to claim 91, wherein:

said pulsing ultraviolet laser beam is pulsed at a repetition rate of at least 50 Hz.

94. The method of performing ophthalmic surgery according to claim 91, wherein:

said pulsing ultraviolet laser beam is sufficient to ablate a depth in a range of 0.05 and 0.5 microns of corneal tissue per pulse.

SUB A12
B15

95. The method of performing ophthalmic surgery according to claim 91, wherein:
said pulsing ultraviolet laser beam provides an energy level of no greater than 10 mJ per pulse to said corneal tissue.

96. The method of performing ophthalmic surgery according to claim 91, wherein:
said ultraviolet laser beam provides an energy level of no greater than 20 mJ per pulse to said corneal tissue.

97. The method of performing ophthalmic surgery according to claim 91, wherein:
successive pulses of said ultraviolet laser beam are overlapped at least 50 percent.

98. The method of performing ophthalmic surgery according to claim 91, wherein:
successive pulses of said ultraviolet laser beam are overlapped in a range of 50 to 80 percent.

99. A method for performing photocoagulation on a corneal surface, comprising:
providing an infrared laser beam;
applying said infrared laser beam onto corneal tissue; and
scanning said infrared laser beam in a pattern to photocoagulate corneal tissue.

SUB A13

100. A method for performing photocoagulation on a corneal surface according to claim 100, wherein:
said infrared laser beam is emitted by a diode laser having a wavelength in a range of 1.54 to 2.5 μm .

101. A method for performing photocoagulation on a corneal surface according to claim 100, wherein:
said infrared laser beam is emitted by a diode laser having a wavelength in a range of 1.9 to 2.5 μm .

102. A method for performing photocoagulation on a corneal surface according to claim 100, wherein:
said infrared laser beam is emitted by a diode laser having a wavelength of 2.1 μm .

103. A method for performing photocoagulation on a corneal surface according to claim 100, wherein:
said infrared laser beam is emitted by a diode laser having a wavelength of 1.54 μm .

ADD A14⁵ >
Add B16 >

SECRET

Inventor(s): J. T. Lin
Appln. No.: 0 / or Patent No.
Filed: May 27, 1998 or Issued:
Title: OPHTHALMIC SURGERY METHOD USING NON-CONTACT
SCANNING LASER

(Atty. Dkt. 62-575)

VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY
STATUS (37 CFR 1.9(d) and 1.27(c)) - **SMALL BUSINESS CONCERN**

I hereby declare that I am

- ☐ the owner of the small business concern identified below:
☒ an official of the small business concern empowered to act on behalf of the concern identified below:

NAME OF CONCERN LaserSight, Incorporated
ADDRESS OF CONCERN 12249 Science Drive, Suite 160
Orlando, Florida 32826

I hereby declare that the above identified small business concern qualifies as a small business concern as defined in 13 CFR 121.12, and reproduced in 37 CFR 1.9(d), for purposes of paying reduced fees under Section 41(a) and (b) of Title 35, United States Code, in that the number of employees of the concern, including those of its affiliates, does not exceed 500 persons. For purposes of this statement, (1) the number of employees of the business concern is the average over the previous fiscal year of the concern of the persons employed on a full-time, part-time or temporary basis during each of the pay periods of the fiscal year, and (2) concerns are affiliates of each other when either, directly or indirectly, one concern controls or has the power to control the other, or a third party or parties controls or has the power to control both.

I hereby declare that rights under contract or law have been conveyed to and remain with the small business concern identified above with regard to the invention **entitled:** OPHTHALMIC SURGERY METHOD USING NON-CONTACT SCANNING LASER

by inventors(s) J. T. Lin described in

X ☐ the Specification filed herewith,
one ☒ Application No. 0 / , filed
box ☒ Patent No. 5,520,679 , issued May 28, 1996

I acknowledge the duty to file, in this case, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

NAME OF PERSON SIGNING William I. Kern

TITLE OF PERSON OTHER THAN OWNER Vice President of Corporate Development

ADDRESS OF PERSON SIGNING 159 Durham Place, Longwood, Florida 32779

SIGNATURE  DATE 5/24/98

**DECLARATION AND POWER OF ATTORNEY FOR REISSUE APPLICATION
BY ASSIGNEE AND INVENTOR**

We, Dr. J. T. Lin and William I. Kern in support of the reissue declaration of inventor and assignee, declare and state as follows:

1. We believe that Dr. J. T. Lin is the original, first and sole inventor of the invention entitled OPHTHALMIC SURGERY METHOD USING NON-CONTACT SCANNING LASER described and claimed in Letters Patent No. 5,520,679 issued on May 28, 1996 from original Application No. 08/218,319 filed March 25, 1994, which is a Continuation-in-Part of Application No. 07/985,617, filed December 3, 1992, and described and claimed in the foregoing attached reissue application. We do not believe that this invention was known or used in the United States before Dr. J. T. Lin's invention thereof, or patented or described in any publication in any country before his invention thereof or more than one year prior to the original application dates of December 3, 1992 or March 25, 1994, or in public use or on sale in the United States more than one year prior to the original application dates of December 3, 1992 or March 25, 1994. This invention has not been patented in any country foreign to the United States prior to the date of the original application on an application filed by Dr. J. T. Lin or his legal representatives or assigns more than 12 months before his original application. We have reviewed and understand the contents of specification and claims as amended by the attached reissue application.

2. Dr. J. T. Lin's residence, post office address and citizenship are as stated below next to his signature.

Certificate Under 37 C.F.R. § 3.73(b)

3. LaserSight, Incorporated certifies that it is the assignee of the entire right, title, and interest in U.S. Patent No. 5,520,679 by virtue of the assignment from Dr. J. T. Lin of Application Serial No. 08/218,319, filed March 25, 1994, recorded on reel 6939 at frame 975. A copy of the assignment is attached herewith.

4. William I. Kern is the Vice President of Corporate Development of LaserSight, Incorporated and he is authorized to act on behalf of assignee. William I. Kern's residence, post office address, and citizenship are as stated below next to his signature.

Consent of Assignee

5. The assignee consents to the accompanying application for reissue.

Reason for Requesting Reissue

6. We now understand and believe that certain language is unnecessarily limiting and its inclusion in the claims of U.S. Patent No. 5,520,679 is an error introduced by prior counsel, who apparently failed to appreciate the significance of the invention. Thus, we believe the original U.S. Patent No. 5,520,679 contains an error that occurred without deceptive intent that renders the patent partly inoperative as a legal document by reason of the patentee claiming less than he had a right to claim.

Summary of Prosecution File History

7. For the Examiner to fully understand the circumstances which gave rise to the decision to file this reissue application, the invention and the prosecution history of Application No. 08/218,319 are summarized.

Patent Application Serial No. 08/218,319 was filed on March 25, 1994, claiming priority from parent Application Serial No. 07/985,617, filed December 3, 1992.

Application Serial No. 08/218,319 included claims directed to a method of performing corneal refractive surgery by reshaping a portion of the corneal surface using a laser.

Original claim 1 recited:

selecting a laser having a pulsed output beam of predetermined ultraviolet wavelength and having an energy level less than 10 mJ/pulse;

selecting a scanning mechanism for scanning said selected laser output beam;

coupling said laser beam to a scanning device for scanning said laser beam over a predetermined surface area;

focusing said scanning laser beam onto the corneal surface of a patient's eye to a predetermined spot size;

aligning the center of the said scanning laser beam onto the patient's eye corneal surface with a visible aiming beam; and

controlling the scanning mechanism to deliver the scanning laser beam in a predetermined overlapping pattern onto a plurality of positions on the corneal surface to photoablate or photocoagulate the corneal tissue whereby a patient's vision is corrected by reshaping of the corneal surface of the patient's eye.

In a first Official Action, dated April 4, 1995, the Examiner rejected claims 1-25 for informal reasons, claims 1, 12-19, 24 and 25 as allegedly being anticipated by U.S. Patent No. 4,729,372 (L'Esperance) under 35 U.S.C. § 102(b) and claims 3-13 and 20-23 as allegedly being obvious over L'Esperance under 35 U.S.C. § 103. In particular,

the Examiner alleged that L'Esperance "discloses a method and apparatus for performing laser surgery on the eye as claimed, including the steps of coupling the laser to a scanning device 14 to deliver a scanned beam to the corneal surface." The Examiner admitted that L'Esperance does not disclose "the particular parameters recited" in the claims, but alleged that to provide L'Esperance "with the particular irradiation ranges and parameters recited would have been obvious to an artisan of ordinary skill in the art for facilitating the corrective therapeutic outcomes."

An Amendment responsive to the first Official Action was filed on August 4, 1995. Claims 1, 2, 5-12, 14-19 and 25 were amended to address informalities. Claim 1 was also amended to recite the removal of from .05 to .5 microns of corneal tissue per pulse. The Applicant argued that L'Esperance did not teach using an irradiation energy level of 10 mJ/pulse or less or removal of from 0.5 to .5 microns of corneal tissue per pulse as recited. The Applicant pointed out that L'Esperance proliferated the use of conventional high power laser beam equipment by teaching the removal of 14 microns of tissue per pulse, i.e., 42 times the maximum amount recited in claim 1 of the application.

In a second Official Action dated November 21, 1995, the Examiner rejected claims 1 and 5-25 under 35 U.S.C. § 103 as allegedly being obvious over L'Esperance. Claims 2-4 were deemed to include informal errors but nevertheless to recite allowable subject matter. The Examiner correctly understood that the invention was "directed towards reducing the size and power of the laser for performing this surgery." The Examiner admitted that L'Esperance disclosed laser power far outside of the claimed range, i.e., having a maximum power of 200 mJ/pulse in a disclosed embodiment which removes 14 microns of tissue per pulse.

An Amendment responsive to the second Official Action was filed on December 22, 1995. Claim 1 was amended to incorporate the subject matter of allowable claim 2, claims 3 and 4 were amended to be dependent upon claim 1, and claim 25 was canceled. The Amendment was entered and the Examiner issued a Notice of

Allowability on January 31, 1996, and U.S. Patent No. 5,520,679 issued on May 28, 1996.

How the Error Was Discovered

8. Through consultation with counsel, the Assignee became aware that the presence of language relating to a visible aiming beam in claim 1 was not required to distinguish from the prior art, nor was the feature ever discussed in the file history.

The Error Was Made Without Deceptive Intent

9. All errors being corrected by the request for re-issue of Patent No. 5,520,679 were made without deceptive intent.

How the Error is Corrected

10. To correct the error, new claims 24 through 98 have been added which do not require a "visible aiming beam." The Applicant had a right to claim the invention without requiring a "visible aiming beam," as is clear from a review of the prosecution history and cited art.

For instance, in the Notice of Allowability dated January 31, 1996, the Examiner stated the following reasons for allowance:

"... the claims now set forth a specific method for performing corneal refractive surgery which includes the steps of selecting a particular laser source and scanning mechanism, and controlling the scanning mechanism to remove a specific amount of corneal tissue through the use of a low power laser. The prior art fails to anticipate or fairly suggest the method steps as set forth in the claims."

We now understand and believe that the language relating a visible aiming beam is unnecessarily limiting and its inclusion in the claims is an error introduced by our prior counsel, who apparently failed to appreciate the significance of the invention. The "visible aiming beam" feature was not argued or even referred to by the Applicant or by the examiner during prosecution of the subject '679 patent. Thus, the new claims presented herewith which do not recite a visible aiming beam should be allowed over the prior art of record for the same reasons the Examiner allowed the claims of the subject '679 patent.

Support for New Claims

11. No new matter has been added by new claims 24 through 104. Support for each of the following new claims can be found in the parent Application Serial No.

07/985,617, filed on December 3, 1992, inter alia as follows:

New claim 24 at page 6, line 19, page 10, line 20, and page 19, line 25;

New claims 25, 49, 79, 84 and 95 at page 6, lines 12-13;

New claims 26, 50 and 96 at page 15, line 7;

New claim 27 at page 19, line 14;

New claims 28-31, 40 and 57-59 at page 13, line 10 and page 19, line 16;

New claims 32, 41, 60, 72 and 97 at page 13, line 9;

New claims 33, 34, 43, 62, 70 and 93 at page 10, line 15;

New claims 35, 44 and 63 at page 15, lines 22-23;

New claims 37, 46 and 65 at page 23, lines 1-2;

New claims 38, 47, 66 and 89 at page 23, line 17;

New claims 39 and 76 at page 13, lines 9-13, and page 15, line 7;

New claims 42, 61 and 92 at page 19, line 25;

New claim 48 at page 6, line 11, page 14, lines 8-10, page 15, line 22 through page 16, line 7, page 23, lines 21-29, and Figs. 6A-6D;

Support for new claim 90 can be found at patent claim 1.

Acknowledgment of Duty of Disclosure

12. We acknowledge the duty to disclose to the United States Patent and Trademark Office information which is material to the examination of this reissue application in accordance with 37 C.F.R. §1.56(a).

Offer to Surrender Patent

13. We request that we may be allowed to surrender, and hereby offer to surrender our said U.S. Letters Patent No. 5,520,679 before allowance of the reissue application, and that Letters Patent may be issued for the same invention upon the foregoing amended specification and claims.

Power of Attorney and Correspondence Address


14. We hereby appoint the registered patent attorney's represented by **Customer No. 20736** to prosecute this reissue application and transact all business in the U.S. Patent and Trademark Office connected herewith. Please direct all correspondence to:

**William H. Bollman
Farkas & Manelli, PLLC
2000 M Street, N.W., 7th Floor
Washington, D.C. 20036-3307
Tel: (202) 261-1000
Fax: (202) 861-0336**

Re-issue Declaration
Patent No. 5,520,679
Page 9

15. We declare that all statements made herein of our own knowledge are true and that all statements made on information and belief are believed to be true; and further that the statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of this reissue application or any patent issued thereon.

Inventor's Signature: _____

Date: May 21, 1998


Inventor's Name: J. T. Lin U.S.A.
First Middle Initial Family Name Country of Citizenship

Residence (City): Winter Springs (State/Foreign Country) Florida

Post Office Address (Include Zip Code): 730 Willow Run lane, Winter Springs,
Florida 32792

Assignee: LaserSight, Incorporated

Signature: _____

Date: 5/21/98

By: William I. Kern U.S.A.
First Middle Initial Family Name Country of Citizenship


Assignee's Title: Vice President of Corporate Development, LaserSight, IncorporatedResidence (City): Longwood (State/Foreign Country) Florida

Post Office Address (Include Zip Code): 159 Durham Place
Longwood, Florida 32779

202233 443000

United States Patent & Trademark Office

Office of Initial Patent Examination -- Scanning Division



Application deficiencies found during scanning:

1. Application papers are not suitable for scanning and are not in compliance with 37 CFR 1.52 because:
 - ☐ All sheets must be the same size and either A4 (21 cm x 29.7 cm) or 8-1/2" x 11". Pages _____ do not meet these requirements.
 - ☐ Papers are not flexible, strong, smooth, non-shiny, durable, and white.
 - ☐ Papers are not typewritten or mechanically printed in permanent ink on one side.
 - ☐ Papers contain improper margins. Each sheet must have a left margin of at least 2.5 cm (1") and top, bottom and right margins of at least 2.0 cm (3/4").
 - ☐ Papers contain hand lettering.
2. Drawings are not in compliance and were not scanned because:
 - ☐ The drawings or copy of drawings are not suitable for electronic reproduction.
 - ☐ All drawings sheets are not the same size. Pages must be either A4 (21 cm x 29.7 cm) or 8-1/2" x 11".
 - ☐ Each sheet must include a top and left margin of at least 2.5 cm (1"), a right margin of at least 1.5 cm (9/16") and a bottom margin of at least 1.0 cm (3/8").
3. Page(s) _____ are not of sufficient clarity, contrast and quality for electronic reproduction.
4. Page(s) _____ are missing.
5. OTHER: NO DRAWING(S)